



FLAT SPLIT - Heat & Cool T1 R410a

AMD 014 **24K BTU**

EAN: 800 3437 95666 9

AMD 013 **18K BTU**

EAN: 8003437956652

AMD 012 **12K BTU**

EAN: 800 3437 95664 5

AMD 014 **Indoor U.** **Outdoor**

Dimensions (WxHxD)	1025x315x227	914x702x312
Weight (Kg)	12	54

AMD 013 **Indoor U.** **Outdoor**

Dimensions (WxHxD)	920x313x223	912x637x285
Weight (Kg)	11	44

AMD 012 **Indoor U.** **Outdoor**

Dimensions (WxHxD)	770x240x179	804x482x240
Weight (Kg)	8	26

Key features

- Single Split
- A energy Class
- New Flat design
- Green LED Display with set temperature displayed
- New remote control
- Removable & washable panel

Features

- 6TH SENSE function
- JET function
- Sleep function for the night
- 24h Timer
- 3 fan speed and Auto Indoor Fan Control
- Dehumidification function
- Swing button to set vertical airflow control
- Auto-restart after blackout

Filters

- Electrostatic filter
- Photo catalytic filter

Others

- Rotary compressor
- No plug mounted



	FLAT SPLIT			
MODEL NUMBER	AMD 014	AMD 013	AMD 012	
Air conditioner type	24K	18K	12K	
	Split - Display	Split -Display	Split-Display	
	Heat / Cool	Heat / Cool	Heat / Cool	Heat / Cool
PERFORMANCES				
Cooling capacity - BTU/h	24.000	19.000	11.700	9.000
Cooling capacity - Watt	7034	5569	3429	2638
Heating capacity - BTU/h	25.000	20.000	12.300	9.400
Heating capacity - Watt	7327	5862	3605	2755
EER cooling (Btu/watt hr)	10,95	10,96	10,96	10,96
COP for cooling (w/w)	3,21	3,21	3,21	3,21
Energy Class (cooling/heating)	A/B	A/A	A/D	A/B
Noise level - Indoor Unit (dBA) - max	49	46	37	35
Noise level - Indoor Unit (dBA) - min	43	42	33	32
Noise level - Outdoor Unit (dBA)	60	54	52	52
Dehumidification - Liters/h	2,7	2,4	1,5	1,2
Air Flow - max (CFM)	960	800	450	420
Refrigerant type	R410A	R410A	R410A	R410A
Refrigerant charge volume (kg)	2,06	1,55	1	0,74
Climate Class	T1	T1	T1	T1
FEATURES				
6 TH SENSE	•	•	•	•
TURBO cool (Jet)	•	•	•	•
Timer on-off 24h	•	•	•	•
Temperature display on remote control	•	•	•	•
Key lock on remote control	-	-	-	-
Sleep Mode	•	•	•	•
Automatic air swing	-	-	-	-
Fan Only	•	•	•	•
No. of cooling/heating speeds	-	-	-	-
Twin Flaps	-	-	-	-
Auto restart after blackout	•	•	•	•
Auto Defrost for outdoor unit	•	•	•	•
Removable, washable Panel	-	-	-	-
Compressor type	Rotary	Rotary	Rotary	Rotary
CONTROLS				
Remote Control	•	•	•	•
AIR PURIFICATION				
Anti dust filter - washable	•	•	•	•
Electrostatic filter	•	•	•	•
HEPA filter	-	-	-	-
PHOTIC CATALYST	•	•	•	•
ELECTRICAL RATINGS				
Volts/Frequency (Hz)	220-240/50	220-240/50	220-240/50	220-240/50
Fuse Size (Amps)	13	10	7	5
Ampere (A) - cooling	10,83	8,13	5,05	3,88
Power input (W) - cooling	7034	5569	3429	2638
Ampere (A) - heating	10,62	7,61	0,02	0,02
Power input (W) - heating	7327	5862	3605	2755
LRA (Lock Rotor Amps)	60	40	28	18
Power Cord Length (m) - Cabinet to Wall	NA	1,5	1,5	1,5
DIMENSIONS				
Net Indoor Unit (WidthxHeightxDepth) (mm)	1025x315x227	920x313x223	770x240x179	770x240x179
Outdoor Unit (WidthxHeightxDepth) (mm)	914x702x312	912x637x285	804x482x240	804x482x240
Weight indoor/outdoor (Kg)	14/54	11/44	6/26	6/26
Container load 20 cu.ft.	72	70	118	128
Container load 40 cu.ft.	128	150	255	273
Container load 40 HC cu.ft.	148	173	308	318

- Available
- Not available



FLAT SPLIT - Heat & Cool T1 R22

AMD 324 **24K BTU**

EAN: 800 3437 95694 2

AMD 323 **18K BTU**

EAN: 800 3437 95693 5

AMD 322 **12K BTU**

EAN: 800 3437 95692 8

Key features

- Single Split
- New Flat design
- Green LED Display with set temperature displayed
- New remote control
- Removable & washable panel

Features

- 6TH SENSE function
- JET function
- Sleep function for the night
- 24h Timer
- 3 fan speed and Auto Indoor Fan Control
- Dehumidification function
- Swing button to set vertical airflow control
- Auto-restart after blackout

Filters

- Photo catalytic filter
- Electrostatic filter

Others

- Rotary compressor
- No plug mounted

AMD 324	Indoor U.	Outdoor
Dimensions (WxHxD)	920x313x223	840x540x244
Net weight	14	41

AMD 323	Indoor U.	Outdoor
Dimensions (WxHxD)	1025x313x203	832x702x380
Net weight	16	58

AMD 322	Indoor U.	Outdoor
Dimensions (WxHxD)	770x240x179	804x431x240
Net weight	8	26



MODEL NUMBER	FLAT SPLIT		
	AMD 324	AMD 323	AMD 322
Air conditioner type	24K	18K	12K
	Split	Split	Split
	Heat/Cool	Heat/Cool	Heat/Cool
PERFORMANCES			
Cooling capacity - BTU/h	22000	18000	11500
Cooling capacity - Watt	6448	5275	3370
Heating capacity - BTU/h	24.000	19.000	12.000
Heating capacity - Watt	7034	5569	3517
EER cooling (Btu/watt hr)	9,18	9,93	8,91
COP for cooling (w/w)	2,69	2,91	2,61
Energy Class (cooling/heating)	C/D	C/C	D/D
Noise level - Indoor Unit (dBA) - max	50	44	37
Noise level - Indoor Unit (dBA) - min	42	38	32
Noise level - Outdoor Unit (dBA)	60	58	54
Dehumidification - Liters/h	2,7	2,4	1,5
Air Flow - max (CFM)	960	800	450
Refrigerant type	R22	R22	R22
Refrigerant charge volume (kg)	1,82	1,34	0,82
Climate Class	T1	T1	T1
FEATURES			
6 TH SENSE	•	•	•
TURBO cool (Jet)	•	•	•
Timer on-off 24h	•	•	•
Temperature display on remote control	-	-	-
Key lock on remote control	-	-	-
Sleep Mode	•	•	•
Automatic air swing	•	•	•
Fan Only	•	•	•
No. of cooling/heating speeds	3	3	3
Twin Flaps	•	-	-
Auto restart after blackout			
Auto Defrost for outdoor unit			
Removable, washable Panel			
Compressor type	Rotary	Rotary	Rotary
CONTROLS			
Remote Control	•	•	•
AIR PURIFICATION			
Anti dust filter - washable	•	•	•
Electrostatic filter	•	•	•
HEPA filter	-	-	-
PHOTIC CATALYST	-	-	-
ELECTRICAL RATINGS			
Volts/Frequency (Hz)	220-240/50	220-240/50	220-240/50
Fuse Size (Amps)	13	10	7
Ampere (A) - cooling	11,3	8,6	6,1
Power input (W) - cooling	2397	1813	1291
Ampere (A) - heating	11,23	7,83	5,77
Power input (W) - heating	2376	1657	1221
LRA (Lock Rotor Amps)	62	52	39
Power Cord Length (m) - Cabinet to Wall	1,5	1,5	1,5
DIMENSIONS			
Net Indoor Unit (WidthxHeightxDepth) (mm)	1025x315x227	920x313x223	770x240x179
Outdoor Unit (WidthxHeightxDepth) (mm)	830x637x285	755x540x255	715x482x240
Weight indoor/outdoor (Kg)	14/46	11/41	8/26
Container load 20 cu.ft.	72	98	116
Container load 40 cu.ft.	151	205	250
Container load 40 HC cu.ft.	170	217	284

- Available
- Not available



FLAT SPLIT - Heat & Cool T3 R22

AMD 334 **24K BTU**

EAN: 800 3437 95705 5

AMD 333 **18K BTU**

EAN: 800 3437 95704 8

AMD 332 **12K BTU**

EAN: 800 3437 96611 8

Key features

- New Flat design
- Green LED Display with set temperature displayed
- New remote control
- Removable & washable panel

Features

- 6TH SENSE function
- JET function
- Sleep function for the night
- 24h Timer
- 3 fan speed and Auto Indoor Fan Control
- Dehumidification function
- Swing button to set vertical airflow control
- Auto-restart after blackout

Filters

- Ion washable filter
- HEPA filter

Others

- Rotary compressor
- No Plug mounted

AMD 334	Indoor U.	Outdoor
Dimensions (WxHxD)	1035x315x227	914x702x312
Net Weight (Kg)	12	54

AMD 333	Indoor U.	Outdoor
Dimensions (WxHxD)	920x313x223	912x637x285
Net Weight (Kg)	11	44

AMD 332	Indoor U.	Outdoor
Dimensions (WxHxD)	770x240x179	840x540x255
Net Weight (Kg)	8	33



	FLAT SPLIT		
MODEL NUMBER	AMD 334	AMD 333	AMD 332
Air conditioner type	24K	18K	12K
	Split	Split	Split
	Cool Only	Cool Only	Cool Only
PERFORMANCES			
Cooling capacity - BTU/h	24000	18600	12500
Cooling capacity - Watt	7034	5451	3664
Heating capacity - BTU/h	-	-	-
Heating capacity - Watt	-	-	-
EER cooling (Btu/watt hr)	9,04	10,70	9,21
COP for cooling (w/w)	7,16	7,51	6,82
Energy Class (cooling/heating)	-	-	-
Noise level - Indoor Unit (dBA) - max	50	44	40
Noise level - Indoor Unit (dBA) - min	42	39	34
Noise level - Outdoor Unit (dBA)	60	58	53
Dehumidification - Liters/h	2,7	2,4	1,5
Air Flow - max (CFM)	960	800	450
Refrigerant type	R22	R22	R22
Refrigerant charge volume (kg)	1,52	1,3	0,84
Climate Class	T3	T3	T3
FEATURES			
6 TH SENSE	•	•	•
TURBO cool (Jet)	Jet	Jet	Jet
Timer on-off 24h	•	•	•
Temperature display on remote control	•	•	•
Key lock on remote control	-	-	-
Sleep Mode	•	•	•
Automatic air swing	•	•	•
Fan Only	•	•	•
No. of cooling/heating speeds	3	3	3
Twin Flaps	-	-	-
Auto restart after blackout	•	•	•
Auto Defrost for outdoor unit	-	-	-
Removable, washable Panel	•	•	•
Compressor type	Rotary	Rotary	Rotary
CONTROLS			
Remote Control	•	•	•
AIR PURIFICATION			
Anti dust filter - washable	•	•	•
Electrostatic filter	-	-	-
HEPA filter	•	•	•
PHOTIC CATALYST	-	-	-
ELECTRICAL RATINGS			
Volts/Frequency (Hz)	220-240/50	220-240/50	220-240/50
Fuse Size (Amps)	13	10	7
Ampere (A) - cooling	11,9	8,3	6,1
Power input (W) - cooling	2654	1848	1357
Ampere (A) - heating	-	-	-
Power input (W) - heating	-	-	-
LRA (Lock Rotor Amps)	65	59	39
Power Cord Length (m) - Cabinet to Wall	NA	1,5	1,5
DIMENSIONS			
Net Indoor Unit (WidthxHeightxDepth) (mm)	1025x315x227	920x313x223	770x240x179
Outdoor Unit (WidthxHeightxDepth) (mm)	832x702x312	830x637x285	755x540x255
Weight indoor/outdoor (Kg)	14/54	11/44	8/33
Container load 20 cu.ft.	62	70	116
Container load 40 cu.ft.	128	150	250
Container load 40 HC cu.ft.	147	173	284

- Available
- Not available



WINDOW – Cool only T3 R22

AMD 398 **24K BTU**

EAN: 800 3437 96613 2

AMD 396 **18K BTU**

EAN: 800 3437 96612 5

Key features

- Rotary compressor
- No plug mounted
- Removable & washable panel
- Fan Function
- Swing button to set vertical airflow control
- Auto-restart after blackout

AMD 398

Dimensions (WxHxD) 660x430x695
Net Weight (Kg) 63

AMD 396

Dimensions (WxHxD) 660x430x695
Net Weight (Kg) 61

MODEL NUMBER	WINDOW	
	AMD 398	AMD 396
Air conditioner type	24K	18K
	Window	Window
	Cool Only	Cool Only
PERFORMANCES		
Cooling capacity - BTU/h	24000	18000
Cooling capacity - Watt	7034	5275
Heating capacity - BTU/h	-	-
Heating capacity - Watt	-	-
EER cooling (Btu/watt hr)	5,63	5,97
COP for cooling (w/w)	1,65	1,75
Energy Class (cooling/heating)	-	-
Noise level - Indoor Unit (dBA) - max	60	60
Noise level - Indoor Unit (dBA) - min	54	54
Noise level - Outdoor Unit (dBA)	65	65
Dehumidification - Liters/h	2,2	1,6
Air Flow - max (CFM)	1000	1000
Refrigerant type	R22	R22
Refrigerant charge volume (kg)	1,02	1,02
Climate Class	T3	T3
FEATURES		
6 TH SENSE	-	-
TURBO cool (Jet)	-	-
Timer on-off 24h	-	-
Temperature display on remote control	-	-
Key lock on remote control	-	-
Sleep Mode	-	-
Automatic air swing	•	•
Fan Only	•	•
No. of cooling/heating speeds	-	-
Twin Flaps	-	-
Auto restart after blackout	•	•
Auto Defrost for outdoor unit	-	-
Removable, washable Panel	•	•
Compressor type	Rotary	Rotary
CONTROLS		
Remote Control	-	-
AIR PURIFICATION		
Anti dust filter - washable	•	•
Electrostatic filter	-	-
HEPA filter	-	-
PHOTIC CATALYST	-	-
ELECTRICAL RATINGS		
Volts/Frequency (Hz)	220-240/50	220-240/50
Fuse Size (Amps)	15	13
Ampere (A) - cooling	14	10
Power input (W) - cooling	3464	2596
Ampere (A) - heating	-	-
Power input (W) - heating	-	-
LRA (Lock Rotor Amps)	59	49
Power Cord Length (m) - Cabinet to Wall	1,5	1,5
DIMENSIONS		
Net Indoor Unit (WidthxHeightxDepth) (mm)	660x430x695	660x430x695
Outdoor Unit (WidthxHeightxDepth) (mm)	750x528x797	750x528x797
Weight indoor/outdoor (Kg)	63 / 66	61 / 64
Container load 20 cu.ft.	84	84
Container load 40 cu.ft.	180	180
Container load 40 HC cu.ft.	225	225

- Available
- Not available